

Two Glass Sliding Door CounterLine Remote

Range: BackBar

SKOPE ID: CL412

Dimensions: 1585 mm (W) × 690 mm (D) × 830 mm (H)*

Capacity: 345 L

* Height with castors is adjustable from 820 to 840.

Project: _____

Item #: _____



A glass door under-bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 32°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The glass doors are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. Sliding door locks are optional. The built-in LED lights provide optimum merchandising and can be dimmed or timed to turn on and off via a free smartphone app. This fridge is designed to be fitted to a remote refrigeration unit (supplied by others) running on R134a, R404A, or as specified at the time of order. The fridge comes fitted with a thermal expansion valve, solenoid valve, and ball valves. It has copper liquid and suction loops to be connected to the remote unit. Other valve options are available on order. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.




Warranty



GEMS



SKOPE-connect



Cabinet

Type	CounterLine		
Finish	Powder-coated galvanised steel or stainless steel		
Insulation	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)	
Doors	Type	Glass sliding door (double-glazed, low-e, argon-filled)	
	Opening Size	Height (mm)	538
		Width (mm)	511
Shelving	Four adjustable height powder-coated wire shelves 4 × outer shelf (547W × 530D)		
Lighting*	1 × 16 W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling		

Dimensions†

	External	Internal	Packed
Width (mm)	1585	1120	TBC
Depth (mm)	690	565	TBC
Height (mm)	820 to 840 (standard castors)	545	TBC
	725 (plinth mount)		
Weight (kg)	160		TBC
Capacity (L)	345		
Footprint (m²)	1.09		

Ventilation/Clearance (mm)

Take into account remote services location.

Top	Not required	Sides	Not required	Rear	Not required
-----	--------------	-------	--------------	------	--------------

Product Loading

Facing	330 ml can	32	600 ml bottle	28
Loading	330 ml can	256	600 ml bottle	196

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet		Multiple cabinets	
			At each joint	At each end wall
Less than 1 metre	±5 mm		±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm		-5 mm to +10 mm	+15 mm

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)	
Maximum Ambient Temperature (°C)	32	
Sound Level (dB(A))	Standard	< 60
	Hush Mode	< 60

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	TBC
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	5.40 kWh/24 h
Annual Running Costs	\$591 (@ \$0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	1.9 power cord with 3-pin, 10 amp plug
Current Draw (A)	2.0

Remote Services

Location	Rear or base			
Drain Size	OD 19 mm			
Pipe Connection	Liquid line	OD 6.35 mm	Suction line	OD 9.52 mm

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)			
System Type	Remote cartridge			
Cartridge Weight (kg)	16			
Refrigerant/Charge	Thermostatic expansion valve fitted to suit refrigerant (R134a or R404A standard)/Nitrogen holding charge			
Nominal Capacity (W)	n.a.			
Heat Rejection (W)	Average	n.a.	Peak	n.a.
Remote Duty (W)	390			
Defrost Type	Automatic, off-cycle			



CL.2.GSL.r
on the SKOPE website

* Accessible via the free SKOPE-connect™ app.