

Serve Over Counter Plug-in



Standard features

- Ventilated cooling, fast cooling
- Self-contained Secop compressor, plug in for use
- R290 gas
- LED light under top
- Dixell digital thermostat
- With back refrigerated storage cabinet
- With intermediate ambient glass shelf
- SUS201 interior
- Custom color

Specifications

Models	SLIM 100C/R	SLIM 130C/R	SLIM 150C/R	SLIM 200C/R	SLIM 250C/R
Exterior Dimensions	1000*900*1200 mm	1300*900*1200 mm	1500*900*1200mm	2000*900*1200mm	2500*900*1200mm
TDA	0.63 m2	0.83 m2	0.96 m2	1.29 m2	1.63 m2
Temperature	0 - +6 °C				
Gross Volume	85 L	110 L	130 L	175 L	220 L
Cooling System	Ventilated	Ventilated	Ventilated	Ventilated	Ventilated
Refrigerant	R290	R290	R290	R290	R290
Voltage/Frequency	220-240V, 50Hz				
Input Power	395 W	405 W	537 W	639 W	800 W
Defrost Power	-	-	-	-	-
Power Consumption	4.7KWH/24H	5.4KWH/24H	6.6KWH/24H	8.5KWH/24H	10.6KWH/24H
Compressor	SC10CNX	SC10CNX	SC12CNX.2	SC15CNX.2	SC18CNX.2
Thermostat	Dixell	Dixell	Dixell	Dixell	Dixell
Cond. Fan Motor	EBM	EBM	EBM	EBM	EBM
Body Material	Exterior Powder Coated Galvanized Steel			Interior: SUS201	
Net Weight	130 KGS	150 KGS	180 KGS	240 KGS	290 KGS
Gross Weight	145 KGS	165 KGS	200 KGS	260 KGS	315 KGS

Sectional Drawing

