



BackBar 2 Glass Swing Door CounterLine Fridge

Model ID: CL.2.GSW

Low height premium two swing door bar fridge featuring dimmable LED lights, lockable doors, and eco-friendly natural refrigerant technology. Designed to fit under the bar.



3 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Maximise storage and display – height allows for 1 row of standard 750ml wine or Riesling bottles, two rows of 355ml beer bottles, two rows of 600ml PET bottles, or four rows of standard beer cans per door
- Market-leading dimmable LED full height strip lighting
- Quieter running with built-in hush mode
- Unrivalled energy efficiency – up to 63% reduction in energy consumption, saving up to \$750 a year on your power bill
- Truly green natural refrigeration technology
- Self-closing swing doors with built in locking tabs on every door
- Fully front-breathing interchangeable modular cartridge for quicker, safer servicing
- NB: A benchtop is not included with this model. The pictured product includes an optional benchtop, which can be priced and supplied separately

SPECIFICATIONS

- Dimensions: 1585 W x 680 D x 830 (with castors - adjustable from 820 to 835) or 725 (with plinth mount) H (mm)
- Doors: 2
- Door Type: Glass - Swing
- Shelves: Four adjustable height, powder-coated wire shelves, 4 x outer shelf (547W x 530L)
- Material: Powdercoat galvanised steel or stainless steel
- Gross Volume (Litres): 345
- Total Floor Area (m²): 1.07
- Weight (kg): 168
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect 0°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 81g
- GEMS Class: 3M1
- GEMS Energy Consumption (kWh/24h): 1.87
- GEMS Annual Running Costs: \$205 (@ \$0.30/kWh)
- kW: 0.62
- Current Draw (Amps): 2.6
- Noise Measurement (dB): Standard <66 Hush Mode (via SKOPE-connect) <62
- Interior Lighting: 1 x 16W, cool white (5500-6500K) LED strip on cabinet ceiling
- Controller: SCS Connect (SKOPE-connect™ compatible)
- Refrigeration System: Removable cartridge
- Power Cord: 1.9m power cord with 3-pin, 10 amp plug
- Power Supply: 220-240 volts a.c., 50 Hz, single phase supply

OPTIONS

- Black exterior/black interior finish
- Stainless Steel Finish
- White exterior/white interior finish
- Designer Door Options
- Extra Shelf & Clips (per level)
- Flat S/S Benchtop
- Passthrough
- Plinth Mounting
- Punched S/S Shelves (per cabinet)
- Right Hand Services
- Solid Doors
- Tropical Heated Glass
- Viewing Panel at End