



BME1200N-A 2 Glass Door Display or Storage Fridge

Model ID: BME1200N-A

ActiveCore 2: durability, power economy and app-based control. Affordable double glass door commercial display fridge offering premium performance and quality, with 1079 litres of eye-level display space.



5 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- The bottom mount configuration drives sales by displaying more product at eye-level
- Save time restocking with 80 product facings (600ml PET bottle)
- Reduce power bills and boost your environmental credentials with market-leading natural refrigerant technology that has virtually no impact on the environment
- Minimize waste and maximize ROI with the SKOPE-connect commercial fridge management app built into every ActiveCore 2 fridge
- Reduce display fridge repair costs and business downtime with the ActiveCore interchangeable refrigeration system for safe, streamlined servicing
- Designed and tested for hot commercial environments of up to 40°C
- Significantly reduced noise for a quieter working environment
- GEMS compliant

SPECIFICATIONS

- Dimensions: 1280 W x 795 D x 2005 H (mm)
- Doors: 2
- Door Type: Glass
- Shelves: 5 (per door)
- Material: Powdercoat galvanised steel
- Gross Volume (Litres): 1079
- Total Floor Area (m²): 1.08
- Weight (kg): 245
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect 1°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 99g (natural refrigerant)
- GEMS Class: 3M1
- GEMS Energy Consumption (kWh/24h): 3.37
- GEMS Annual Running Costs: \$369 p.a. (@ \$0.30/kWh)
- kW: 0.72
- Current Draw (Amps): 3.0 (includes unit 2.6)
- Electrical Safety Climate Class: 5
- Interior Lighting: 2 x 1370mm, 15W LED
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Bottom mounted, integral, removable ActiveCore refrigeration unit (UBHCNI-0008)
- Power Cord: Supplied with 2.0m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50Hz, single phase supply

OPTIONS

- Black exterior/black interior finish
- White exterior/white interior finish
- Branded Decals Print (Sign, Sides & Kick Panel)
- Extra Shelf & Clips (per level)
- Gravity Matting
- Lit Sign (See AC Model)
- Merchandising Strips