



Nine Drawer, Three Bay, Underbench GN 1/1 Fridge

Model ID: PG11.UBR.3.D9

A chef's precision is crafted into every detail with the ProSpec. Setting the new benchmark for commercial refrigeration, including a sleek, clean aesthetic, full configurability, high-spec performance and integrated food safety data collection. Mould the ProSpec to work for you. Mix and match your desired number of bays, doors, drawers or both. Available in left or right hand services.



FEATURES & BENEFITS

- 2 Drawers per Door;#3 Drawers per Door;#Plinth Mounting;#Remote Refrigeration Unit;#Right Hand Services
- Unlock the power of SKOPE-connect, including its enhanced pre-sets. Simply press a button to switch between general food safe, poultry, red meat, fresh seafood, live seafood, dairy and desserts temperature ranges

SPECIFICATIONS

- Dimensions: 1750 W x 700 D x 850 H (mm)
- Material: 304 AISI stainless steel
- Gross Volume (Litres): 432
- Total Floor Area (m²): 1.23
- Refrigeration Unit: Self-Contained
- Temperature Range: 1 to 4 (adjustable from -2 to 15 with SKOPE-connect)
- Max Ambient Temperature: 40
- Refrigerant: R290 / 95g (natural refrigerant)
- GEMS Class: 5M1
- GEMS Energy Consumption (kWh/24h): 3.14 kWh/24 h
- GEMS Annual Running Costs: \$344 (@ \$0.30/kWh)
- kW: .48
- Current Draw (Amps): 2.0
- Noise Measurement (dB): 65 (adjustable to 63 with SKOPE-connect Hush Mode)
- Controller: SCS Connect (SKOPE-connect compatible)
- Refrigeration System: Removable cartridge
- Power Cord: 2 m power cord with 3-pin, 10 amp plug
- Power Supply: 220-240 volts a.c. 50Hz, single phase supply

OPTIONS