

The SKOPE logo is displayed in white, bold, uppercase letters on a red rectangular background.

ProSpec 1 Solid Door Upright GN 2/1 Fridge

Model ID: PG21.UPR.1.SD

ProSpec offers chefs, consultants and architects a high-performance gastronorm solution. All the features of the award-winning ReFlex series but with a cutting edge look and an upgrade to ActiveCore™ swappable cartridges.



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Extra Runners;#Extra S/S Shelf;#Extra Shelf & Slides
- Unlock the power of SKOPE-connect, including its enhanced pre-sets. Simply press a button to switch between general food safe, poultry, red meat, fresh seafood, live seafood, dairy and desserts temperature ranges

SPECIFICATIONS

- Dimensions: 730 W x 865 D x 2185-2200 H (mm)
- Doors: 1
- Door Type: Self-closing, lockable, solid swing door with stay open position at 90°C
- Shelves: 5 stainless steel GN 2/1 adjustable wire shelves on a fully removable and cleanable racking system
- Material: 304 AISI stainless steel interior and exterior on all faces
- Gross Volume (Litres): 572
- Total Floor Area (m²): 0.63
- Weight (kg): 150
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect 1°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 99g (natural refrigerant)
- GEMS Class: 5M1
- GEMS Energy Consumption (kWh/24h): 2.20
- kW: 0.72
- Current Draw (Amps): 3.0 (includes unit 2.6)
- Electrical Safety Climate Class: 5 (40°C/40% RH)
- Interior Lighting: 1 x 1400mm, 16W LED light (door activated)
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Top mounted, integral, removable ActiveCore refrigeration unit (UTHCBI-0010)
- Power Cord: Supplied with 2.3m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS