

The SKOPE logo is displayed in white, bold, uppercase letters on a red rectangular background.

ProSpec 2 Solid Door Upright GN 2/1 Freezer

Model ID: PG21.UPF.2.SD

Heavy duty gastronorm flexibility in an ultra-tough, premium 304 stainless steel two solid door freezer. Transfer pans with ease in a package offering the very best in SKOPE engineering for busy venues, from natural refrigerant technology to easy clean design features.



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Extra Runners;#Extra S/S Shelf;#Extra Shelf & Slides
- Full 304 stainless steel design and build

SPECIFICATIONS

- Dimensions: 1410 W x 865 D x 2185 (with castors - adjustable from 2185 to 2200) or 2245 with legs H (mm)
- Doors: 2
- Door Type: Solid
- Shelves: Ten adjustable height, stainless steel GN 2/1 shelves (530W x 650L)
- Material: 304 AISI stainless steel
- Gross Volume (Litres): 1266
- Total Floor Area (m²): 1.21
- Weight (kg): 260
- Refrigeration Unit: Self-Contained
- Temperature Range: -21 to -18 (adjustable* from -26 to -12)
- Max Ambient Temperature: 40
- Refrigerant: R290 / 137 g
- GEMS Class: 5L1
- GEMS Energy Consumption (kWh/24h): 14.89
- GEMS Annual Running Costs: \$1,630 (@ \$0.30/kWh)
- kW: 1.32
- Current Draw (Amps): 5.5
- Noise Measurement (dB): Standard 66 Hush Mode (via SKOPE-connect) 63
- Interior Lighting: 2 x 1400 mm, 16 watt LED lights (door-activated)
- Controller: SCS Connect (SKOPE-connect™ compatible)
- Refrigeration System: Removable cartridge
- Power Cord: 3 m power cord with 3-pin, 10 amp plug
- Power Supply: 220-240 volts a.c., 50 Hz, single phase supply

OPTIONS