



ReFlex 1 Solid Door Upright Fridge

Model ID: RF7.UPR.1.SD

ReFlex leverages the power of SKOPE-connect to let you switch between ideal temperature settings at the touch of an app. This 1 door fridge also offers typical SKOPE durability and power economy on a footprint of just 0.52m².



3 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Unlock the power of SKOPE-connect, including its enhanced pre-sets. Simply press a button to switch between general food safe, poultry, red meat, fresh seafood, live seafood, dairy and desserts temperature ranges
- 304 Stainless Steel body and SKOPE design quality ensure tough durability for back of house duties
- Reduce costs with cutting-edge power economy
- Experience peace of mind with a natural refrigerant that has virtually no impact on the environment
- Easy-to-service refrigeration cartridge system
- Premium-look contemporary design promotes usability and modern working environment for staff
- GEMS compliant

SPECIFICATIONS

- Dimensions: 680 W x 760 D x 1985 H (mm)
- Doors: 1
- Door Type: Self-closing, lockable, reversible, solid swing doors
- Shelves: 5 adjustable plastic coated wire shelves
- Material: 304 AISI stainless steel interior and exterior
- Gross Volume (Litres): 469
- Total Floor Area (m²): 0.52
- Weight (kg): 115
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect -2°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 70g (natural refrigerant)
- GEMS Class: 5M1
- GEMS Energy Consumption (kWh/24h): 2.00
- GEMS Annual Running Costs: \$219 p.a. (@ \$0.30/kWh)
- kW: 0.48
- Current Draw (Amps): 2.0 (includes unit 1.5)
- Electrical Safety Climate Class: 5
- Interior Lighting: 1 x 1200mm, 12W LED light (door activated)
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Top mounted, integral, removable refrigeration cartridge (UTKCNI-0017)
- Power Cord: Supplied with 2m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS

- Extra Shelf & Clips (per level)