

SKOPE®



ReFlex 2 Glass Door Underbench GN 1/1 Compatible Fridge

Model ID: RF7.UBR.2.GD

Meet the first glass door underbench model in the ReFlex series. It gives you all the strength and innovation you expect, plus complete visibility of the food you're keeping cool.



3 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Convenient glass door visibility complemented by premium-look contemporary design that promotes usability
- Unlock the power of SKOPE-connect, including its enhanced pre-sets. Simply press a button to switch between general food safe, fresh seafood, live seafood, chocolate, drinks, dairy and desserts temperature ranges.
- 304 Stainless Steel body and SKOPE design quality ensure tough durability for back of house duties
- Minimise power costs carbon footprint with cutting-edge natural refrigerant technology
- Easy-to-service refrigeration cartridge system
- Stainless steel benchtop as standard
- GN Compatible - fits GN 1/1 trays
- GEMS compliant

SPECIFICATIONS

- Dimensions: 1290 W x 730 D x 850 H (mm)
- Doors: 2
- Door Type: Self-closing, lockable, double glazed, double Low-E, glass swing doors
- Shelves: 2 per door - 1 adjustable, 1 floor mounted
- Material: 304 AISI stainless steel interior and exterior
- Gross Volume (Litres): 248
- Total Floor Area (m²): 0.94
- Weight (kg): 116
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect -2°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 80g (natural refrigerant)
- GEMS Class: 4M1
- GEMS Energy Consumption (kWh/24h): 2.39
- GEMS Annual Running Costs: \$262 p.a. (@ \$0.30/kWh)
- kW: 0.48
- Current Draw (Amps): 2.0 (includes unit 1.5)
- Electrical Safety Climate Class: 5
- Interior Lighting: 1 x 400mm, 4W LED light
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Sie mounted, integral, removable refrigeration cartridge (ULKCN1-0027)
- Power Cord: Supplied with 2m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS

- Extra Shelf & Clips (per level)
- GN Runners (1 pair)
- GN Slide Kit (2 levels)