



ReFlex 2 Solid Door GN Compatible Salad Preparation Fridge

Model ID: RF7.PPS.2.SD

Award-winning ReFlex technology brings unbeatable food safety value to food preparation with this two solid-door, gastronorm salad prep station. A food-grade 304 stainless steel body and SKOPE-connect help protect internal food safety, while new features like fan-forced ducted airflow offer greater food safety protection across the benchtop.



3 Year Warranty Protection



SKOPE-connect™



Natural Refrigerant



ChillGuard™



FEATURES & BENEFITS

- Supplied with stainless steel benchtop and 4 x 1/3 100mm deep gastronorm pans
- Includes a removable 200mm, 13mm thick cutting board
- Designed to hold 1/3 and 1/6 gastronorm pans in the pot wells, inside the fridge is compatible with 1/1 gastronorm pans
- Class-leading food safety and reliability technology: fan-forced ducted airflow, full 304 stainless steel body, condensation mitigation system, e-coated evaporation coils, and optimised blown air well
- SKOPE-connect: be alerted if internal temperature changes threaten to waste food and change temperature range on-the-go
- Reduce costs with cutting-edge power economy – up to 30% more efficient than market benchmark
- Experience peace of mind with a natural refrigerant that has virtually no impact on the environment
- Small, easy-to-service refrigeration cartridge system saves you time and gives you more internal shelf space

SPECIFICATIONS

- Dimensions: 1270 W x 700 D x 1110 H (mm)
- Doors: 2
- Door Type: Self-closing, lockable, solid swing doors
- Shelves: 2 adjustable wire shelves per door + base
- Material: 304 AISI stainless steel interior and exterior
- Gross Volume (Litres): 217
- Total Floor Area (m²): 0.89
- Weight (kg): 139
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect 0°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 90g (natural refrigerant)
- Energy Consumption (kWh/24h): 2.67
- Annual Running Costs: \$292 p.a. (@ \$0.30/kWh)
- kW: 0.48
- Current Draw (Amps): 2.0 (includes unit 1.0)
- Electrical Safety Climate Class: 5
- Interior Lighting: 1 x 400mm, 4W LED light (door activated)
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Side mounted, integral, removable refrigeration cartridge (ULQCNI-0029)
- Power Cord: Supplied with 2m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS

- Extra Shelf & Clips (per level)