

SKOPE®



ReFlex 2 Solid Door Underbench Fridge, 1500mm Wide

Model ID: RF7.UBR.2XL.SD

ReFlex is the underbench food storage fridge that lets you do more. Quickly match temperature range to produce with SKOPE-connect. Enjoy SKOPE design and build quality with this specially designed 1500-wide package.



3 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Unlock the power of SKOPE-connect, including its enhanced pre-sets. Simply press a button to switch between general food safe, poultry, red meat, fresh seafood, live seafood, dairy and desserts temperature ranges
- 304 Stainless Steel body and SKOPE design quality ensure tough durability for back of house duties
- Reduce costs with cutting-edge power economy
- Experience peace of mind with a natural refrigerant that has virtually no impact on the environment
- Easy-to-service refrigeration cartridge system
- Premium-look contemporary design promotes usability and modern working environment for staff
- With a 1500 mm wide body, it has extra capacity, accessible via large doors.
- GEMS compliant

SPECIFICATIONS

- Dimensions: 1500 W x 700 D x 850 (incl 130mm castors) H (mm)
- Doors: 2
- Door Type: Self-closing, lockable, solid swing doors
- Shelves: 2 per door - 1 adjustable, 1 floor mounted
- Material: 304 AISI stainless steel interior and exterior
- Gross Volume (Litres): 333
- Total Floor Area (m²): 1.05
- Weight (kg): 115
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect -2°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 80g (natural refrigerant)
- GEMS Class: 5M1
- GEMS Energy Consumption (kWh/24h): 2.11
- GEMS Annual Running Costs: \$231 p.a. (@ \$0.30/kWh)
- kW: .48
- Current Draw (Amps): 2.0
- Electrical Safety Climate Class: 5
- Interior Lighting: 1 x 400mm, 4W LED light (door activated)
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Side mounted, integral, removable refrigeration cartridge
- Power Cord: 2.3 m power cord with 3-pin, 10 amp plug
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS

- Extra Shelf & Clips (per level)
- GN Runners (1 pair)
- GN Slide Kit (2 levels)