



ReFlex 4 Drawer ChefBase GN 2/1 Fridge

Model ID: RF8.CBR.2.D4

Full stainless steel ChefBase with four lockable refrigerated drawers and a reinforced top with no-drip edge that secures your equipment in place. Built for grills, griddles and cook-tops - and anything else you care to throw at it.



3 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- 400kg load-bearing capacity expands benchtop equipment choice
- SKOPE-connect free app provides food safety alerts and automated temperature recording
- 45mm-thick construction combining food-safe 304 AISI stainless steel with tough fibro-cement insulating heat shield
- Front-breathing refrigeration unit ideal for small spaces, with easy cleaning access to condenser
- Natural refrigerant - absolute minimum carbon footprint and low power consumption
- Stainless steel benchtop with welded no-drip (marine) edge
- GN Compatible - fits 1x GN 1/1 and 3 x 1/6 trays, up to 100mm deep
- GEMS compliant

SPECIFICATIONS

- Dimensions: 1838 W x 815 D x 610 H (mm)
- Doors: 4 Drawers
- Door Type: Full extendable, refrigerated stainless steel drawers with individual key locks
- Material: 304 AISI stainless steel interior and exterior
- Gross Volume (Litres): 371
- Total Floor Area (m²): 1.50
- Weight (kg): 160
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect 0°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 100g (natural refrigerant)
- GEMS Class: 5M1
- GEMS Energy Consumption (kWh/24h): 4.40
- GEMS Annual Running Costs: \$482 p.a. (@ \$0.30/kWh)
- kW: 0.43
- Current Draw (Amps): 1.8
- Electrical Safety Climate Class: 5
- Controller: SCS Connect (SKOPE-connectTM compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Built-in, integral refrigeration system with side mounted condensing unit
- Power Cord: Supplied with 2m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS