

The SKOPE logo is displayed in white, bold, uppercase letters on a red rectangular background.

ReFlex 4 Solid Door Underbench GN 1/1 Compatible Fridge

Model ID: RF7.UBR.4.SD

Enjoy maximum capacity, maximum convenience and maximum toughness with this GN compatible underbench food storage fridge. This 4 door ReFlex comes wrapped in a 304 Stainless Steel body designed for commercial kitchen duties.



3 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Unlock the power of SKOPE-connect, including its enhanced pre-sets. Simply press a button to switch between general food safe, poultry, red meat, fresh seafood, live seafood, dairy and desserts temperature ranges
- 304 Stainless Steel body and SKOPE design quality ensure tough durability for back of house duties
- Reduce costs with cutting-edge power economy
- Experience peace of mind with a natural refrigerant that has virtually no impact on the environment
- Easy-to-service refrigeration cartridge system
- Premium-look contemporary design promotes usability and modern working environment for staff
- GN Compatible - fits GN 1/1 trays
- GEMS compliant

SPECIFICATIONS

- Dimensions: 2210 W x 700 D x 850 H (mm)
- Doors: 4
- Door Type: Self-closing, lockable, solid swing doors
- Shelves: 2 per door - 1 adjustable, 1 floor mounted
- Material: 304 AISI stainless steel interior and exterior
- Gross Volume (Litres): 526
- Total Floor Area (m²): 1.55
- Weight (kg): 155
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect -2°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 95g (natural refrigerant)
- GEMS Class: 5M1
- GEMS Energy Consumption (kWh/24h): 3.77
- GEMS Annual Running Costs: \$413 p.a. (@ \$0.30/kWh)
- kW: 0.48
- Current Draw (Amps): 2.0 (includes unit 1.5)
- Electrical Safety Climate Class: 5
- Interior Lighting: 3 x 400mm, 4W LED light (door activated)
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Side mounted, integral, removable refrigeration cartridge (ULKCN1-0022)
- Power Cord: Supplied with 2m, 10 Amp plug and lead
- Power Supply: 220-240 Volts a.c. 50 Hz, single phase supply

OPTIONS

- Extra Shelf & Clips (per level)
- GN Runners (1 pair)
- GN Slide Kit (2 levels)