Three Solid Door Salad Preparation GN1/3 Fridge

Model ID: PG13.PPS.DC.3.SD

A chef's precision is crafted into every detail with the ProSpec. Setting the new benchmark for commercial refrigeration, including a sleek, clean aesthetic, full configurability, high-spec performance and integrated food safety data collection. Mould the ProSpec to work for you. Mix and match your desired number of bays, doors, drawers or both. Available in left or right hand services.

Three Solid Door Salad Preparation GN1/3 Fridge

Product Code: PG13.PPS.DC.3.SD

FEATURES & BENEFITS

- Barrel Door Locks
- Unlock the power of SKOPE-connect, including its enhanced pre-sets. Simply press a button to switch between general food safe, poultry, red meat, fresh seafood, live seafood, dairy and desserts temperature ranges

SPECIFICATIONS

- Dimensions: 1820 W x 700 D x 845 to 885 (standard legs), 850 (castors), 720 (plinth mount) H (mm)
- Doors: 3
- Door Type: Solid
- Shelves: Six 304 stainless steel wire shelves 6 × shelf (350W × 530D)
- Material: 304 AISI stainless steel
- Gross Volume (Litres): 372
- Total Floor Area (m^2): 1.27
- Weight (kg): 135
- Refrigeration Unit: Self-Contained
- Temperature Range: 1 to 5
- Max Ambient Temperature: 40
- Refrigerant: R290/90 g
- GEMS Class: 5M1
- Noise Measurement (dB): 63.2
- Interior Lighting: 2 × 400 mm, 4 W LED lights (door-activated)
- Controller: SCS Connect (SKOPE-connect™ compatible)
- Refrigeration System: Removable cartridge
- Power Cord: 2 m power cord with 3-pin, 10 amp plug
- Power Supply: 220-240 volts a.c., 50 Hz, single phase supply

OPTIONS