

SKOPE®



TME1000N-A 2 Glass Door Display or Storage Fridge

Model ID: TME1000N-A

ActiveCore 2: durability and power economy combined with app-based control. An affordable double glass door commercial display fridge offering premium performance, quality, and 897 litres of space.



5 Year Warranty Protection



GEMS Compliant



SKOPE-connect™



Natural Refrigerant



FEATURES & BENEFITS

- Pack more in and drive impulse sales with superior display space
- Save time restocking with 70 product facings (600ml PET bottle)
- Reduce power bills and boost your environmental credentials with market-leading natural refrigerant technology that has virtually no impact on the environment
- Minimize waste and maximize ROI with the SKOPE-connect commercial fridge management app built into every ActiveCore 2 fridge
- Reduce display fridge repair costs and business downtime with the ActiveCore interchangeable refrigeration system for safe, streamlined servicing
- Designed and tested for hot commercial environments of up to 40°C
- Significantly reduced noise for a quieter working environment
- GEMS compliant

SPECIFICATIONS

- Dimensions: 1130 W x 745 D x 2200 H (mm)
- Doors: 2
- Door Type: Glass
- Shelves: 5
- Material: Powder coated galvanised steel
- Gross Volume (Litres): 897
- Total Floor Area (m²): 0.84
- Weight (kg): 225
- Refrigeration Unit: Self-Contained
- Temperature Range: 1°C to 4°C (adjustable with SKOPE-connect 1°C to 15°C)
- Max Ambient Temperature: 40°C
- Refrigerant: R290 / 99g (natural refrigerant)
- GEMS Class: 3M1
- GEMS Energy Consumption (kWh/24h): 3.79
- GEMS Annual Running Costs: \$415 p.a. (@\$0.30/kWh)
- kW: 0.72
- Current Draw (Amps): 3.0 (includes unit 2.6)
- Electrical Safety Climate Class: 5
- Interior Lighting: 2 x 1400mm, 15W LED
- Controller: SCS Connect (SKOPE-connect compatible)
- Connectivity: Bluetooth® wireless technology
- Refrigeration System: Top mounted, integral, removable ActiveCore refrigeration unit (UTHCNI-0010)
- Power Cord: Supplied with 2.3m, 10 Amp plug and lead
- Power Supply: 220-240V a.c. 50Hz, single phase supply

OPTIONS

- Branded Decals Print (Sign & Sides)
- Extra Shelf & Clips (per level)
- Gravity Matting
- Lit Sign (See AC Model)
- Merchandising Strips