

## Filter Performance Data - 0.2 Micron

### HEALTH CLAIM PERFORMANCE CERTIFIED BY NSF/ANSI

This system has been tested according to NSF/ANSI Standards 42, 53 and 401 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42, 53 and 401.

| 93701(NZ), 93702(NZ), 93704(NZ)                                               | NHMRC ADWG or USEPA SDWA MCL | Average Influent concentration | NSF/ANSI influent challenge concentration                  | % reduction reqt / Max. permissible product water concentration | Max effluent concentration | Minimum % reduction | Average % removal | Average effluent concentration |
|-------------------------------------------------------------------------------|------------------------------|--------------------------------|------------------------------------------------------------|-----------------------------------------------------------------|----------------------------|---------------------|-------------------|--------------------------------|
| <b>NSF/ANSI 42 - Aesthetic Effects</b>                                        |                              |                                |                                                            |                                                                 |                            |                     |                   |                                |
| Chlorine, Taste and Odor                                                      | 0.6 mg/L                     | 1.92 mg/L                      | 2.0 mg/L $\pm$ 10%                                         | $\geq$ 50%                                                      | 0.06 mg/L                  | 96.8%               | 97.4%             | 0.05 mg/L                      |
| Nominal Particulate Reduction, Class I ( $\geq$ 0.5 $\mu$ m to $<$ 1 $\mu$ m) | -                            | 9,200,000 particles/mL         | at least 10,000 particles/mL                               | $\geq$ 85%                                                      | 190,000 particles/mL       | 98.2%               | 99.0%             | 96,167 particles/mL            |
| <b>NSF/ANSI 53 - Health Effects</b>                                           |                              |                                |                                                            |                                                                 |                            |                     |                   |                                |
| Cysts (3.00 $\pm$ 0.15 $\mu$ m particles)                                     | 99.5% reduction              | 125,000 microspheres/L         | minimum 50,000 microspheres/L                              | $\geq$ 99.95%                                                   | 8 microspheres/L           | 99.99%              | 99.99%            | 8 microspheres/L               |
| Lead (at 6.5 pH)                                                              | -                            | 0.155 mg/L                     | 0.15 mg/L $\pm$ 10%                                        | 0.005 mg/L                                                      | 0.0015 mg/L                | 99.0%               | 99.8%             | 0.0003 mg/L                    |
| Lead (at 8.5 pH)                                                              | -                            | 0.162 mg/L                     | 0.15 mg/L $\pm$ 10%                                        | 0.005 mg/L                                                      | 0.0019 mg/L                | 98.7%               | 99.6%             | 0.0006 mg/L                    |
| Asbestos                                                                      | 7 MFL                        | 20,144,750 fibers/L            | 10 <sup>7</sup> to 10 <sup>8</sup> fibers/L (10 - 100 MFL) | $\geq$ 99%                                                      | 650 fibers/L               | 99.99%              | 99.99%            | 157 fibers/L                   |
| <b>NSF/ANSI 401 -Emerging Compounds/Incidental Contaminants</b>               |                              |                                |                                                            |                                                                 |                            |                     |                   |                                |
| Microplastics, particles 0.5 to $<$ 1 $\mu$ m                                 | -                            | 9,200,000 particles/mL         | at least 10,000 particles/mL                               | $\geq$ 85%                                                      | 190,000 particles/mL       | 98.2%               | 99.0%             | 96,167 particles/mL            |

\*Pressure = 60 psig  $\pm$  3; pH = 7.5  $\pm$  0.5; temp. = 20°  $\pm$  3°C \*United States Environmental Protection Agency (USEPA) Safe Drinking Water Act / New Zealand Ministry of Health Drinking-water Standards for New Zealand

| Class  | Treatment Type            | Function                                                                                                | Pass |
|--------|---------------------------|---------------------------------------------------------------------------------------------------------|------|
| I      | Microbiological Status    | Will stop bacteria increasing, but will not remove unless II (a) is passed.                             | ✓    |
| II     | Microbiological Treatment | Will remove or inactivate bacteria.                                                                     | N/A  |
| II (a) | Bacteria Removal          | Will remove or inactivate bacteria.                                                                     | N/A  |
| II (b) | Virus Removal             | Will remove or inactivate virus.                                                                        | N/A  |
| II (c) | Protozoa Removal          | Cyptosporidium and Giardia. Will not remove or inactivate bacteria unless II (a) and II (b) are passed. | ✓    |
| III    | Particulate Reduction     | Reduces cloudiness.                                                                                     | ✓    |
| IV     | Taste and Odour Reduction | Reduces tastes and odours.                                                                              | ✓    |
| V      | Chemical Treatment        | Decreases certain chemicals: - Lead                                                                     | ✓    |

Legend: = ✓ Pass N/A = Not Applicable

### OPERATING SPECIFICATIONS

- Pressure requirement: 10 -125 psi (0.7 - 8.62 bar), non-shock
- Temperature: 35 -100°F (2-38°C)

| Model                          | Flow Rate | Capacity | Kit # |
|--------------------------------|-----------|----------|-------|
| 0.2mic MicroPurity Filter 1S   | 3.75 Lpm  | 4,163 L  | 93701 |
| 0.2mic MicroPurity filter 1.5S | 3.75 Lpm  | 6,813 L  | 93702 |
| 0.2mic MicroPurity Filter 2S   | 5.678 Lpm | 9,463 L  | 93704 |

Zip filter systems are designed for ease of installation. However, post-installation inspections are highly recommended. Check for leaks immediately after installation and once again after 24 hours. If leaks are detected, turn off water supply, drain water and inspect the leaks. If problem persists, contact the installer / plumber for rectification.

It is essential that operational, maintenance and filter replacement requirements be carried out for this product to perform as advertised.

Flush new cartridge for 10L or at least 2 min 40 seconds to remove trapped air bubbles.

If left unused for more than 24 hours, flush cartridge for 10L or at least 2 min 40 seconds before use.

The compounds certified under NSF/ANSI 401 have been deemed as 'incidental contaminants / emerging compounds'. Incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.

**Note:** While the testing was performed under standard laboratory conditions, actual performance may vary.

This 93701, 93702 and 93704 cartridge is certified by IAPMO R&T in PS-ZIP 0.2 micron system against NSF/ANSI Standard 42 and 53 for the reduction of:

#### STANDARD NO. 42 – AESTHETIC EFFECTS

Bacteriostatic Effects  
Chemical Reduction Unit  
Taste and Odour Reduction  
Chlorine Reduction  
Mechanical Filtration Unit  
Nominal Particulate Reduction, Class I

#### STANDARD NO. 53 – HEALTH EFFECTS

Chemical Reduction Unit  
Lead Reduction  
Mechanical Filtration Unit  
Cyst Reduction  
Asbestos

#### STANDARD NO. 401 – Emerging Compounds/Incidental Contaminants

Microplastics

\* The term "bacteriostatic" indicates that the system limits the passage or growth of bacteria that may already exist in the incoming water. It does not mean that water leaving the system is safer to drink than water entering the system.



\*Filter system certified by IAPMO R&T against NSF 42, 53 and 401; against NSF 372 for lead free product. Models 93701 and 93702 are certified against CSA B483.1

## Filter Performance Data - 3 Micron

### HEALTH CLAIM PERFORMANCE CERTIFIED BY NSF/ANSI

This system has been tested according to NSF/ANSI 42 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42.

| 93703(NZ), 93705(NZ)                                     | NHMRC ADWG or USEPA SDWA MCL | Average Influent concentration | NSF/ANSI influent challenge concentration | % reduction reqt / Max. permissible product water concentration | Max effluent concentration | Minimum % reduction | Average % removal | Average effluent concentration |
|----------------------------------------------------------|------------------------------|--------------------------------|-------------------------------------------|-----------------------------------------------------------------|----------------------------|---------------------|-------------------|--------------------------------|
| <b>NSF/ANSI 42 - Aesthetic Effects</b>                   |                              |                                |                                           |                                                                 |                            |                     |                   |                                |
| Chlorine, Taste and Odor                                 | 0.6 mg/L                     | 2.16 mg/L                      | 2.0 mg/L ± 10%                            | ≥ 50%                                                           | 0.05 mg/L                  | 97.7%               | 99.2%             | 0.02 mg/L                      |
| Nominal Particulate Reduction, Class II (1 µm to < 5 µm) | -                            | 4,200,000 particles/mL         | at least 10,000 particles/mL              | ≥ 85%                                                           | 270,000 particles/mL       | 93.7%               | 97.7%             | 95,167 particles/mL            |

\*Pressure = 60 psig ± 3; pH = 7.5 ± 0.5; temp. = 20° ± 3°C \*United States Environmental Protection Agency (USEPA) Safe Drinking Water Act / New Zealand Ministry of Health Drinking-water Standards for New Zealand

| Class  | Treatment Type            | Function                                                                                                | Pass |
|--------|---------------------------|---------------------------------------------------------------------------------------------------------|------|
| I      | Microbiological Status    | Will stop bacteria increasing, but will not remove unless II (a) is passed.                             | ✓    |
| II     | Microbiological Treatment | Will remove or inactivate bacteria.                                                                     | N/A  |
| II (a) | Bacteria Removal          | Will remove or inactivate bacteria.                                                                     | N/A  |
| II (b) | Virus Removal             | Will remove or inactivate virus.                                                                        | N/A  |
| II (c) | Protozoa Removal          | Cyptosporidium and Giardia. Will not remove or inactivate bacteria unless II (a) and II (b) are passed. | N/A  |
| III    | Particulate Reduction     | Reduces cloudiness.                                                                                     | ✓    |
| IV     | Taste and Odour Reduction | Reduces tastes and odours.                                                                              | ✓    |
| V      | Chemical Treatment        | Decreases certain chemicals: - Lead                                                                     | N/A  |

Legend: = ✓ Pass N/A = Not Applicable

This 93703, 93705 and 95230 cartridge is certified by IAPMO R&T in PS-ZIP 3 micron system against NSF/ANSI Standard 42 for the reduction of:

#### STANDARD NO. 42 – AESTHETIC EFFECTS

Bacteriostatic Effects  
Chemical Reduction Unit  
Taste and Odour Reduction  
Chlorine Reduction  
Mechanical Filtration Unit  
Nominal Particulate Reduction, Class II

\* The term “bacteriostatic” indicates that the system limits the passage or growth of bacteria that may already exist in the incoming water. It does not mean that water leaving the system is safer to drink than water entering the system.



\*Filter system certified by IAPMO R&T against NSF 42; against NSF 372 for lead free product.

### OPERATING SPECIFICATIONS

- Pressure requirement: 10 -125 psi (0.7 - 8.62 bar), non-shock
- Temperature: 35 -100°F (2-38°C)

| Model                        | Flow Rate | Capacity | Kit # |
|------------------------------|-----------|----------|-------|
| 3mic MicroPurity filter 1.5S | 3.75 Lpm  | 13,248 L | 93703 |
| 3mic MicroPurity Filter 2S   | 5.678 Lpm | 17,034 L | 93705 |

Zip filter systems are designed for ease of installation. However, post-installation inspections are highly recommended. Check for leaks immediately after installation and once again after 24 hours. If leaks are detected, turn off water supply, drain water and inspect the leaks. If problem persists, contact the installer / plumber for rectification.

It is essential that operational, maintenance and filter replacement requirements be carried out for this product to perform as advertised.

Flush new cartridge for 10L or at least 2 min 40 seconds to remove trapped air bubbles.

If left unused for more than 24 hours, flush cartridge for 10L or at least 2 min 40 seconds before use.

The compounds certified under NSF/ANSI 401 have been deemed as ‘incidental contaminants / emerging compounds’. Incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.

**Note:** While the testing was performed under standard laboratory conditions, actual performance may vary.

## Filter Performance Data - Carbon Free

### HEALTH CLAIM PERFORMANCE CERTIFIED BY NSF/ANSI

This system has been tested according to NSF/ANSI Standards 42, 53 and 401 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standards 42, 53 and 401.

| 93706(NZ)                                                                              | NHMRC ADWG or USEPA SDWA MCL | Average Influent concentration | NSF/ANSI influent challenge concentration | % reduction reqt / Max. permissible product water concentration | Max effluent concentration | Minimum % reduction | Average % removal | Average effluent concentration |
|----------------------------------------------------------------------------------------|------------------------------|--------------------------------|-------------------------------------------|-----------------------------------------------------------------|----------------------------|---------------------|-------------------|--------------------------------|
| <b>NSF/ANSI 42 - Aesthetic Effects</b>                                                 |                              |                                |                                           |                                                                 |                            |                     |                   |                                |
| Nominal Particulate Reduction, Class I ( $\geq 0.5 \mu\text{m}$ to $< 1 \mu\text{m}$ ) | -                            | 1,533,333 particles/mL         | at least 10,000 particles/mL              | $\geq 85\%$                                                     | 140,000 particles/mL       | 93.0%               | 96.4%             | 55,050 particles/mL            |
| <b>NSF/ANSI 53 - Health Effects</b>                                                    |                              |                                |                                           |                                                                 |                            |                     |                   |                                |
| Cysts ( $3.00 \pm 0.15 \mu\text{m}$ particles)                                         | 99.5% reduction              | 130,700 microspheres/L         | minimum 50,000 microspheres/L             | $\geq 99.95\%$                                                  | 17 microspheres/L          | 99.99%              | 99.99%            | 11 microspheres/L              |
| Asbestos                                                                               | 7 MFL                        | 18,525,000 fibers/L            | $10^7$ to $10^8$ fibers/L (10 - 100 MFL)  | $\geq 99\%$                                                     | 128,000 fibers/L           | 99.18%              | 99.57%            | 79,950 fibers/L                |
| <b>NSF/ANSI 401 -Emerging Compounds/Incidental Contaminants</b>                        |                              |                                |                                           |                                                                 |                            |                     |                   |                                |
| Microplastics, particles 0.5 to $< 1 \mu\text{m}$                                      | -                            | 1,533,333 particles/mL         | at least 10,000 particles/mL              | $\geq 85\%$                                                     | 140,000 particles/mL       | 93.0%               | 96.4%             | 55,050 particles/mL            |

\*Pressure = 60 psig  $\pm$  3; pH = 7.5  $\pm$  0.5; temp. = 20°  $\pm$  3°C \*United States Environmental Protection Agency (USEPA) Safe Drinking Water Act / New Zealand Ministry of Health Drinking-water Standards for New Zealand

| Class  | Treatment Type            | Function                                                                                                | Pass |
|--------|---------------------------|---------------------------------------------------------------------------------------------------------|------|
| I      | Microbiological Status    | Will stop bacteria increasing, but will not remove unless II (a) is passed.                             | ✓    |
| II     | Microbiological Treatment | Will remove or inactivate bacteria.                                                                     | N/A  |
| II (a) | Bacteria Removal          |                                                                                                         |      |
| II (b) | Virus Removal             | Will remove or inactivate virus.                                                                        | N/A  |
| II (c) | Protozoa Removal          | Cyptosporidium and Giardia. Will not remove or inactivate bacteria unless II (a) and II (b) are passed. | N/A  |
| III    | Particulate Reduction     | Reduces cloudiness.                                                                                     | ✓    |
| IV     | Taste and Odour Reduction | Reduces tastes and odours.                                                                              | N/A  |
| V      | Chemical Treatment        | Decreases certain chemicals: - Lead                                                                     | N/A  |

Legend: = ✓ Pass N/A = Not Applicable

### OPERATING SPECIFICATIONS

- Pressure requirement: 10 -125 psi (0.7 - 8.62 bar), non-shock
- Temperature: 35 -100°F (2-38°C)

| Model                          | Flow Rate | Kit # |
|--------------------------------|-----------|-------|
| 0.2mic MicroPurity Filter 1.5S | 5.678 Lpm | 93706 |

Zip filter systems are designed for ease of installation. However, post-installation inspections are highly recommended. Check for leaks immediately after installation and once again after 24 hours. If leaks are detected, turn off water supply, drain water and inspect the leaks. If problem persists, contact the installer / plumber for rectification.

It is essential that operational, maintenance and filter replacement requirements be carried out for this product to perform as advertised.

Flush new cartridge for at least 2 minutes to remove trapped air bubbles.

If left unused for more than 24 hours, flush cartridge for 2 minutes before use.

The compounds certified under NSF/ANSI 401 have been deemed as 'incidental contaminants / emerging compounds'. Incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.

**Note:** While the testing was performed under standard laboratory conditions, actual performance may vary.

This 93706 cartridge is certified by IAPMO R&T in PS-ZIP 0.2 micron system against NSF/ANSI Standard 42 and 53 for the reduction of:

**STANDARD NO. 42 – AESTHETIC EFFECTS**

- Bacteriostatic Effects
- Mechanical Filtration Unit
- Nominal Particulate Reduction, Class I

**STANDARD NO. 53 – HEALTH EFFECTS**

- Mechanical Filtration Unit
- Cyst Reduction
- Asbestos

**STANDARD NO. 401 – Emerging Compounds/Incidental Contaminants**

- Microplastics

\* The term “bacteriostatic” indicates that the system limits the passage or growth of bacteria that may already exist in the incoming water. It does not mean that water leaving the system is safer to drink than water entering the system.



\*Filter system certified by IAPMO R&T against NSF 42, 53 and 401; against NSF 372 for lead free product. Certified against CSA B483.1.

Refer to User Guide for operation and maintenance.



**Zip Water  
(Aust)**

67 - 77 Allingham Street, Condell Park NSW 2200  
Postal: Locked Bag 80, Bankstown 1885  
Australia  
Tel (+612) 9796 3100  
Free call 1800 947 827 (1800 ZIP TAP)  
[www.zipwater.com](http://www.zipwater.com)

**Zip Water  
(UK)**

Trafalgar House, Rash's Green,  
Dereham, Norfolk, NR19 1JG  
0345 6 005 005  
[sales@zipindustries.co.uk](mailto:sales@zipindustries.co.uk)  
[specify.zipwater.co.uk](http://specify.zipwater.co.uk)

**Zip Water  
(NA)**

9399 West Higgins Road, Suite 1100  
Rosemont, IL 60018  
Free call 1-833-233-2358  
[www.na.zipwater.com](http://www.na.zipwater.com)



As Zip policy is one of continuous product improvement, changes to specifications may be made without prior notice. Images in this booklet have been modified and may not be true representations of the finished goods.

The terms "Zip" and "HydroTap" are registered trade marks of Zip Heaters (Aust) Pty Ltd.

Manufactured by Paragon Water Systems.