

Datasheets

Stand II model 6-2/1, 10-2/1 - MobilityLine



Articlenumber

60.31.165

Description

The iCombi Pro oder iCombi Classic 6-1/1 and 10-1/1 is fixed to the MobilityLine base frame II using a mounting kit. Side bars protect the cooking system and together with the large stable castors, they facilitate mobility.

Intended use

This product is intended exclusively for professional use, such as in restaurant kitchens or catering operations for schools, hospitals, or delis. Any other use runs counter to its intended purpose, and could be dangerous. RATIONAL AG assumes no liability for consequences of improper use.

Features

- 14 support rails with 62 mm rail distance
- Two-sided opening with side panels and top panel
- Mounting kit for fixing the cooking system on the base frame
- Securing the containers against slipping
- 4 stainless steel castors, Ø 200 mm diameter
- Support with impact protection brackets

Capacity

1/1 GN	Grid	7 x	2/1 GN	7 x
1/1 GN	20 mm deep	7 x	2/1 GN	7 x
1/1 GN	40 mm deep	7 x	2/1 GN	7 x
1/1 GN	65 mm deep	4 x	2/1 GN	4 x
1/1 GN	100 mm deep	3 x	2/1 GN	3 x

Verwendung sonstiger Behälter: 1/4 GN, 1/3 GN, 1/2 GN, 2/3 GN, 2/4 GN

Technical specifications

Width of racks:	330 mm
Clearance from bottom rack to floor panel:	68 mm
Clearance from floor panel to floor:	180 mm
Max. fixed power:	600 kg

Dimensions and weights

Width (W):	1.421 mm
Height (H):	789 mm
Depth (D):	1.084 mm
Weight:	105,3 kg

Material

Rust-free stainless steel (CNS 1.4301/AISI 304)

